



# INSTALLATION INSTRUCTIONS

www.vikingbags.com

888-208-1949 | support@vikingbags.com

## SADDLEBAG INSTRUCTION WITH FAT BRACKETS

### Parts

- Fat bracket x 4
- Hex Head Bolts (Long) x 4 (with Nuts and Washers)
- Bolts (Small) x 4
- Spacers (0.25 and 0.5 inches)




Fig (A)

### Tools Required

- Adjustable wrench
- Drill
- Screw driver



Fig (B)

### Instructions

#### Step 1

Open the top straps. Loop each strap around the guard as shown in the image and then secure the straps using the plastic rectangles and the Velcro. Repeat for the bottom straps.



Fig (C)

#### Step 2

Once the bag is in your desired position, continue holding the bag in the position and mark the fender bolt positions on the back of the bag. These points will be used to mount the bag.




Fig (D)



# INSTALLATION INSTRUCTIONS

www.vikingbags.com

888-208-1949 | support@vikingbags.com

## **Step 3**

With the bag laying on the floor, place the fat bracket on the back of the bag such that the uppermost hole in the bracket is aligned with the marked point on the back of the bag and the bottom of the bracket is parallel to the bottom of the bag. With bracket in position, mark the position of the bottom most hole in the bracket. Repeat the same process for the second marked point.

**Note:** For bags with shock cut-out, you may need to position the bracket differently to accommodate the cut-out.

## **Step 4**

Drill the marked points so that corresponding bolts can pass through.



Fig (E)



Fig (F)

## **Step 5**

Using washers, push a Hex Head Bolt (Long) from inside through each of the two upper holes and then through the bracket. The flat side of the bracket should be towards the back of the bag.



Fig (G)

## **Step 6**

With the brackets in position, push a smaller bolt (using washers) through each of the two lower holes in the back of the bag and then through the bottom holes of both brackets. Tighten the small bottom bolts.

## **Step 7**

Now place the saddlebags against the fender and push the Hex Head Bolts into the fender holes and tighten. Your bags are now mounted and ready for a ride



Fig (H)



# INSTALLATION INSTRUCTIONS

[www.vikingbags.com](http://www.vikingbags.com)

 888-208-1949 |  [support@vikingbags.com](mailto:support@vikingbags.com)

## Note

In case the bolts are too long and there is a risk that they may hit the tire, pass the Upper Hex Head Bolts through a spacer first before passing them through the back of the bag and the bracket.

## Warnings

- ✓ Avoid usage of any mounting part that is impaired or is not working properly.
- ✓ If you are not secure about the installation of the saddlebags, do not use them.
- ✓ Sporadically check for shifting of the bag and verify that no part of the mounting system is interfering with any part of the motorcycle while riding. This includes the drive train, suspension, brakes or wheels.
- ✓ It is important to note that if you do not mount these saddlebags properly damage may be caused to the saddlebags and/or motorcycle.
- ✓ If bags are securely installed, no part of the mounting system or bags should touch the motorcycle while in operation.
- ✓ Do not attempt to use these saddlebags if the mounting instructions are unclear. It is important that you seek professional assistance from a qualified mechanic or dealer.